

JETCAM

4.0



Basics:

Highend steelcart with:
1/2" water connection with BSP female thread
Waterfilter
Pressure gauge
Hand crank with gear ratio
10" tablet holder
Camera holder
Reel brake
Pneumatik tyres
Rails to unload
Accesory bag

Optronic GmbH Industriestraße 53 | D-87448 Waltenhofen Tel.: +49 (0)831/ 28885
contact@optronic.de | www.optronic.de Geschäftsführung: Caroline Riezler
Sitz: Waltenhofen Amtsgericht Kempten: HRB 15590

Control unit 4.0:
Controllable via tablet with Sewerlink App
Protection class IP 64
Data type-in
Light regulation
Recording and project management
Battery display
Location 512 Hz
Precise gravitational meter counter

Battery:
Lithium Ion Battery
Power cable with magnetic connection
Working hours > 7 h



Camerahead:	Incl. impact guard
Diameter range:	DN 50 - 300
Steerable from:	DN 50
Housing:	Stainless steel, Ø 32 mm, 50mm
Resolution:	560 TV lines/ PAL
Optic:	Wideanglevision, 145°
Focus:	Fix
Illumination:	9 LEDs up to DN 300
Waterproof:	IP68 min. 5 bar

Optronic GmbH Industriestraße 53 | D-87448 Waltenhofen Tel.: +49 (0)831/ 28885
 contact@optronic.de | www.optronic.de Geschäftsführung: Caroline Riezler
 Sitz: Waltenhofen Amtsgericht Kempten: HRB 15590

Steeringpart:

Hp hose 35 cm, electronically assembled with steering nozzle

Standart cleaning nozzle ENZ with 6 jets, screwable

Plugable at camera head side

**HP-Hose JetCam:**

Surface reinforced, very abrasion resistant and flexible hp-hose, electrically fully assembled at both ends

1 SC steelbraid for extreme durability and well protected, inner wire

Colour: black

Working pressure: 3/8" 180 bar, 1/2" 160 bar

DN 10 (3/8") or DN 12 (1/2")

Standart length 60 m

Dimensions:

Weight: 54 kg

Folded down:(LxWxH) 63 x 49 x 80 cm

Optronic GmbH Industriestraße 53 | D-87448 Waltenhofen Tel.: +49 (0)831/ 28885
contact@optronic.de | www.optronic.de Geschäftsführung: Caroline Riezler
Sitz: Waltenhofen Amtsgericht Kempten: HRB 15590

Optional:



Nozzle Set ENZ

Nozzlecase incl.:

- 6- and 12- jet cleaning nozzle,
- 1/2" HRH, KBR and Rotopuls rotation nozzle
- Front jet nozzle incl. mugel (protection for camera head)
- Steering part, screwable
- Jet cleaning set, protection oil, tools

Ø 40mm 1/2" HRH/KBR/Roto

60 l/min. - 100 Bar

Nozzles for 1/2" systems, exchangeable on steering part

Ø 40mm 1/2" HRH-Rotation Nozzle

Ø 40mm 1/2" KBR-Rotation Nozzle

Ø 40mm 1/2" Rotopuls-Rotation Nozzle

Nozzles for 3/8" systems

Ø 28mm 3/8" HRH 40 l/min. 100 Bar/ incl. and crimped on steering part

Front jet nozzle

Pressure < 90-100 Bar = activated

Pressure > 90-100 Bar = deactivated

Hose extension

20 m 1/2" hose extension